



X-05 COMPARED TO X-03SE

	X-05	X-03SE
Primary application	2 ch. audiophile	2 ch. audiophile / Reference grade
Mechanism type	VRDS	VRDS
Mechanism materials (proprietary).	Bulk moulded compound (BMC) for tray and frame. BMC is a hybrid compound of glass, resins and carbon fiber. Stronger and denser than any known plastic. Metal surround and hybrid steel bridge.	Die cast aluminum and steel including steel bridge.
Disc clamp	Aluminum and polycarbonate / full size clamping	Cut aluminum / full size clamping
SACD/CD capable	Yes	Yes
SACD playback mode	DSD	PCM at 88.2 kHz
SACD multi-channel capable	Yes, with optional i.LINK audio output	Yes, i.LINK output included
Internal DACs	Cirrus Logic x 2 per ch.	Burr-Brown x 2 per ch.
Up-conversion	24 bit / 192 kHz fixed	24 bit / 96 kHz fixed
Dual mono 2 ch. design	Yes	Yes
Optical pick-up	P-03 series	P-03 series
Power supplies	Single toroidal	Dedicated analog plus dedicated digital
WORD sync input	Yes	Yes
Internal wiring	Below 6N copper	6N copper
WBT output terminals	No	Yes
Capacitors and resistors	Below P-01 grade	P-01 grade
Colors available	Silver/Black	Silver
Weight	39 lbs.	52 lbs.
MSRP	\$6,000	\$8,200